

TECHNICAL DATA SHEET

Updating of the document : 08/08/2019
Document ISO reference: DON/LS 03.1112.A



NITFOX HIGH S3 SRC HRO

ANKLE BOOT IN BLACK
WATER REPELLENT LEATHER
PU/NITRILE SOLE

PROTECTIONS FOR THIS MODEL



Available sizes : from 39 (6) to 47 (12)
Weight of one pair in size 42 : 1370 gr.
Norm EN ISO 20345 : 2011
CERTIFICATION N° :0075/007/161/08/19/2374

Upper features

- Upper : black water repellent grained leather split
- Collar : synthetic
- Tongue : synthetic
- Lining : tridimensional textile
- Vamp lining : synthetic
- Back part : synderm
- Eyelet : metallic
- Laces : polyamide
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

Protections

- Toecap : non metallic polycarbonate (200 joules)
- Midsole : anti-perforation insert in stainless steel (1100 Newtons)

Fitting features

- Natur'form (large)
- Lasting : California
- Lasting insole : textile
- Footbed : foam and textile

Sole features

- Name : C07
- Material : polyurethane / nitrile
- Comfort sole density : 0,5
- Comfort sole color : dark grey
- Outsole density : 1
- Outsole color : black
- Slip resistance SRA (flat) : 0.40 ; (heel) : 0.40
- Slip resistance SRB (flat) : 0.17 ; (heel) : 0.13

Requirements of the norm EN ISO 20345

-  Steel toecap
-  Polycarbonate toecap
-  Aluminum toecap (200 joules)
-  Steel midsole
-  Non metallic midsole
- A** A Electric resistance – Antistatic shoes.
- CI** CI Insulating sole against cold.
- E** E Heel energy absorption.
- Fo** FO Hydrocarbons resistance of the undermine sole.
- Hi** HI Insulating sole against heat.
- Hro** HRO Heat resistance of the sole.
- M** M Metatarsal protection.
- P** P Perforation resistance.
- Wru** Wru Water repellent upper.
- Wr** WR Water repellent shoe.



Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) $\geq 0,32$
SRA (heel) $\geq 0,28$
SRB (flat) $\geq 0,18$
SRB (heel) $\geq 0,13$

Advantages = End users benefits

- **Non metallic toecap made of injected polycarbonate** : invisible when worn as lightweight and ergonomic, chemically inert, elastic (in a crash, the toecap back into shape, releasing the foot easily), nonmagnetic (undetected by metal detectors) and thermal insulation (not sensitive to variation and heat transfer between -10 ° C to +40 ° C).
- **2,0 - 2,2mm thickness leather** for better resistance (to abrasion, tearing, perforation) and longer durability.
- **Tridimensional textile lining**, very breathable and soft for higher ventilation of the foot and improved comfort.
- **Retro reflective piping** on the side for better visibility. **Sealed tongue. Few seams and four stitchings** on the side for better solidity.
- **C07 sole** :
 - ✓ **Polyurethane and nitrile sole (PU/Nitrile)**. PU injected for better resistance and comfort and Nitrile resistant to high temperature by contact
 - ✓ **Heel shock absorber**
 - ✓ **Non-slip structure** with a studded open for better drainage of fluids
 - ✓ **Attack heel**, for a natural unfolding of the foot during walking and comfort while driving vehicle
 - ✓ **Open heel** for better security, especially when climbing ladders